10kV busbar heat shrink tubing specifications



Overview

Contraction ratio: 2:1 (1kV, 35kV), 2. 5:1 (10kV bus) Shrinkage temperature:84℃□125℃ Operating temperature:-40℃□125℃ Environmental protection, high strength, good elasticity, flame retardant and softMaterial: Radiation-crosslinked modified polyolefin Shrink ratio: 2. Besides, medium voltage busbar heat shrink tubing is. Made of environment-friendly material 10KV heat shrinkable polyolefin heat shrinkable busbar by high-energy electron beam crosslinking, PBB, PBBD, PBBE limit and heavy metals and other harmful substances to the environment, does not produce toxic and harmful substances during combustion, can. Applications: BH-BBT-10KV 10KV heat shrink bus bar tubing provides high resistance to tracking and arching and used to enhance the insulation properties of bus bar in switchgear and substation. Be suit to the trend of smaller switch cabinets. Be applied in bus duct for insulation among buses. Constructed from halogen-free, flame-retardant polyolefin, it offers excellent thermal and mechanical durability, along with a reliable 2:1 shrink ratio for optimal fit and coverage.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Article Content

10KV Busbar Heat Shrink Tubing | KTG Electronics | ETW

Material: Radiation-crosslinked modified polyolefin. Shrink ratio: 2.5:1. Medium voltage busbar heat shrink tubing can be used for the insulation protection of medium-voltage switchgear busbar since its

10KV Technical Standard for Heat Shrink Tubing of Busbar

*The indexes for 10KV bus. In the index test, must be the product of differential shrinkage on the bus bar, and to ensure that the thinnest thickness is greater than 2mm, the bus length should be greater

10KV heat shrink bus bar tubing BH-BBT-10KV

Applications: BH-BBT-10KV 10KV heat shrink bus bar tubing provides high resistance to tracking and arching and used to enhance the insulation properties

10kV Flame-Retardant Busbar Sleeve | Heat Shrink Insulating Tubing

High-performance 10,000 Volts Busbar Sleeve with flame-retardant, halogen-free polyolefin. Provides superior electrical insulation, shrink ratio 2:1, UL & RoHS compliant.

10KV Busbar Heat Shrink Tube: High

Specifically designed for 10KV busbars, it offers excellent insulation and protection. Made of high - quality materials, it can withstand high voltage and harsh environments. Ideal for power distribution

All About 10kv Heat Shrink Busbar Tube: Specifications, Performance ...

10kV heat shrink busbar tubes are essential components in modern electrical systems, offering a reliable and efficient solution for insulating and protecting busbars in high-voltage environments.

10kv PVC Low-Pressure Heat Shrink Tube for Low Voltage Insulation ...

Our 10kV PVC heat shrink tube provides superior electrical insulation and protection for low-voltage applications. Engineered with high

SKBT-MV Medium Voltage 10KV Busbar Insulation

SKBT-MV Medium Voltage Heat shrink busbar insulation tubing is a kind of continuous tubing made of radiation cross-linked polyolefin which carries

10KV Technical Standard for Heat Shrink Tubing of Busbar

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Made of environment-friendly material 10KV heat shrinkable polyolefin heat shrinkable busbar by high-energy electron beam crosslinking, PBB, PBBD, PBBE limit and heavy metals and other harmful

3M™ Heat Shrink Tubing BBI | 3M United States

3M™ Bus Bar Heat Shrink Tubing BBI is a flame retardant tubing that provides reliable protection and insulation for 5 to 35 kV rated applications. The cross

Heat Shrink Insulation Tubing

Heat-shrinkable busbar insulation tubing. Busbar heat-shrinkable tubing are suitable for use on long runs of rectangular or round busbars.

BUSBAR INSULATION TUBING BPTM

TE Connectivity''s (TE) Raychem BPTM medium-wall, heat shrink tubing provides insulation enhancement and protection against flashover and accidentally induced discharge. Particularly

HEAT SHRINKABLE SLEEVES/TUBES

HEAT SHRINKABLE SLEEVES/TUBES Heat Shrinkable Sleeves provide insulation enhancement to bus-bar systems up to 36kv and protect them against flashover and accidental induced discharge.

Raychem BBIT/BPTM Busbar Tubing Guide

BBIT and BPTM are heat-shrinkable tubing products used for insulating and reducing clearance on electric busbars ranging from 5-35kV for BBIT and 5-25kV for BPTM. They are flexible tubes that are

Busbar Tubing | Manufacturer of Cable Management Products | KTG

Our heat shrink busbar tubing provides high-performance insulation for busbar protection. It offers environmental friendliness, superior insulation properties, and durability.

Heat Shrink Busbar Tubing | Insulating Tubing | KTG

KTG Electronics provides heat shrink busbar tubing with size from 20mm to 200mm. It is suitable for busbar insulation in electrical substation, high voltage and low

DUWAI HB1.5

The 10KV high-voltage insulated busbar heat shrinkable tube is made of environmentally friendly polyolefin heat shrinkable material cross-linked by high

High Voltage Heat Shrink Busbar Insulation Tubing

© 2026 EXF OPTICAL NETWORKS - All rights reserved

35kV high voltage busbar heat shrink tubing is widely used in the insulation protection of high-voltage switchgear busbars, thanks to its outstanding

Contact Us

Continue your research online:

Website: https://explosivefunctions.co.za
Technical inquiry: https://explosivefunctions.co.za/contact.html
EU project coordination: Parque das Nações, Lisbon, Portugal

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 EXF OPTICAL NETWORKS - All rights reserved