288-core non-ribbon optical cable



Overview

Universal (Indoor/Outdoor) dry core optical fiber Multi Loose Tube cable with aramid yarns as strength member and Low Smoke Zero Halogen outer jacket. Existing out of 12 tubes with a diameter of 2. 5mm with 288 fibers (12t x 24f) MM OM2. Corning ALTOS® all-dielectric gel-free cables are designed for outdoor and limited indoor use for backbones in lashed aerial and duct installations. The loose tube gel-free design is fully waterblocked using craft-friendly, water-swellable materials, which means cable access is simple and no clean. Fiber Indoor/Outdoor cable, TeraSPEED ®, Single Jacket All-Dielectric, 288 fiber, Riser Rated, Gel-Free, Stranded Loose Tube, Singlemode G. A1, Feet jacket marking, Black jacket color Finish making your selections or clear them to view relevant specifications. The fibres shall be ribbonized for easy mass fusion splicing and termination with 12-fibre MPO style connectors. 5mm with 288 fibers (12t x 24f). Our one-of-a-kind QuickTreX® Custom Pre-Terminated Fiber Optic Cable Assemblies are made in the USA and have a longstanding reputation of 25+ years for premium quality and reliability that cannot be beat.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Article Content

760086710 | R-288-LN-8W-F12BK/25D | CommScope

Fiber Indoor/Outdoor cable, TeraSPEED®, Single Jacket All-Dielectric, 288 fiber, Riser Rated, Gel-Free, Stranded Loose Tube, Singlemode G.652.D and G.657.A1, Feet jacket marking, Black jacket color

Opti-Core 144 and 288-Fibre Indoor Ribbon Cables, LSZH and

288 singlemode fibres for high density data center distribution applications. The fibres shall be ribbonized for easy mass fusion splicing and termination with 12-fibre MPO style connectors.

288EU4-T4101D20

The all-dielectric cable construction requires no bonding or grounding, and these cables have a medium-density polyethylene jacket that is rugged, durable and easy to strip.

Multi-Loose Tube Fiber Cable

Universal (Indoor/Outdoor) dry core optical fiber Multi Loose Tube cable with aramid yarns as strength member and Low Smoke Zero Halogen outer jacket. Existing out of 12 tubes with a diameter of

Custom 288 Strand Corning Outdoor Armored SM Fiber Optic

Our outdoor armored pre-terminated fiber optic assemblies are perfect for campus backbones, headend termination to a fiber backbone, and intra-building backbones. They are also designed for a variety of

Indoor/Outdoor Riser Sub-unitized MicroCore® Cable

AFL now offers high fiber count Indoor/Outdoor MicroCore Cables. Waterblocked sub-units are helically stranded to provide sub-unitized cables ranging from 24 to

Meet The Ribbon and Non-Ribbon Optical Cables Moistureproof

It is mainly used for outdoor optical cable connection, wiring and scheduling, and flexibly connects optical cables and fibre cores in optical cables through optical fibre movable connectors and patch

Enbeam OS2 Armoured CST Fibre Optic Cable Loose Tube 288 Core

The singlemode fibre is G.652.D compliant low water peak grade and offers OS2 performance and OS1 backwards compatibility. These compact, lightweight cables are extremely rugged, provide rodent

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Micro Cables | Melbye

288F G657A1 200µm slim micro cable typically used in outdoor microduct installation applications. The cable is suitable for air-blown installation. Cable

SST-UltraRibbon™ 288 F, Gel-Free, Armored

SST-UltraRibbon™ 288 F Single-Tube, Gel-Free, Armored Cable - Corning Corning SST-UltraRibbon™ gel-free cables continue the innovative breakthrough in outdoor cable technology by

288 Core Optical Fiber Cable

Discover 288 core optical fiber cables with high-density core count for FTTH and telecom networks. Ideal for long-distance, high-speed data transmission.

200µm fibers, for use in microducts 288 MicroFlexTM RICT I

OVERVIEW MicroFlex RICT with FlexRibbon® Technology provides an ultracompact indoor/outdoor cable design that contains up to 288 bend insensitive fibers. By using FlexRibbon technology,

Product Spec Sheet 288EV8-14101-A3

Available in fiber counts from 288 to 432, each 24-fiber ribbon can be easily separated by hand into two 12-fiber ribbons. The 12-fiber ribbons have readily identifiable ribbon IDs, fiber

RocketRibbon® Extreme Density Cables | Ribbon Cable

RocketRibbon® Cable Corning''s new RocketRibbon ® cabling solution was developed to meet today''s demand for the highest bandwidth capacity in a duct,

288EU4-T4101D20 | ALTOS® Loose Tube, Gel-Free

Corning ALTOS® all-dielectric gel-free cables are designed for outdoor and limited indoor use for backbones in lashed aerial and duct installations. The loose tube

288 F UltraRibbon™ Indoor, Gel-Free Fiber Optic Cable, Plenum

288 F UltraRibbon™ Indoor, Gel-Free Fiber Optic Cable, Plenum Home Products Fiber Optic Cables Indoor Ribbon Riser 288ZVJ-14101D20 MFQ: CORNING ISO/IEC 11801 Indoor OFNP /

Product Spec Sheet 288TVZ-14180D20

LSZH UltraRibbon cables employ a single buffer tube containing a stack of 24-fiber ribbons that are easily separated by hand into two 12-fiber ribbons respectively. This cable is also available with

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Fibre Optical Multi Loose Tube Cable, Indoor-Outdoor, 288F

Unit Properties Fibre Jelly Filled Loose Tube with Optical Fibre Strength Member Fibre Reinforced Central Strength Member (FRP) PE Coated Waterblocking Agent – CSM Water Blocking Yarn

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://explosivefunctions.co.za
Technical inquiry: https://explosivefunctions.co.za/contact.html
EU project coordination: Parque das Nações, Lisbon, Portugal

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 EXF OPTICAL NETWORKS - All rights reserved