
429 Optical Cable



Overview

Pasternack's PE3FCA429-25M fiber optic breakout cord is a robust and versatile fiber optic cable assembly designed for high-performance data transmission in various environments. This 25-meter long 12-fiber cable assembly is equipped with SC/UPC to ST/UPC connectors. Outstanding balance which reflects all unpaid changes due at this time per your selected payment method. Do not show again and take me directly to the Cart. A tariff of 28% may be. OVP, OCP, SCP Protection (OVP: Over Voltage output Protection. SCP: Short Circuit output Protection) Does Not Contain: Alkaline / Nickel / NIMH or Lithium Ion Batteries. The image shown here is indicative ONLY. It is a drop-in replacement for PIC D620222. To save you time in cable fab, we use a white laser markable jacket. 06) Weight lbs/1000ft (kg/1000m): 16. Imagery is for. Avionics Full-Duplex Switched Ethernet (AFDX), also ARINC 664, is a data network, patented by international aircraft manufacturer Airbus, for safety-critical applications that utilizes dedicated bandwidth while providing deterministic quality of service (QoS).

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Article Content

Search results for: 429 Fiber Optic Cable Assemblies – Mouser

Amphenol ProLabs Fiber Optic Cable Assemblies Dell 470-11429 Compatible TAA Compliant 10GBase-CU SFP+ Direct Attach Cable (Passive Twinax, 1m) Learn More about Amphenol ProLabs cable

Omnihil 5 Feet Mini USB Cable Compatible with Dell DW316

Product Summary: Omnihil 5 Feet Mini USB Cable Compatible with Dell DW316 External USB Slim DVD R/W Optical Drive 429-AAUX

12-Fiber SC UPC to ST UPC, OM1 Multimode Distribution Cable,

Pasternack''s PE3FCA429-25M fiber optic breakout cord is a robust and versatile fiber optic cable assembly designed for high-performance data transmission in various environments. This 25-meter

GF70-22A429 Laser-Markable ARINC 429 Cable

GF70-22A429 cable designed per the ARINC 429 Data Bus specification. Drop-in replacement for PIC D620222. White laser markable jacket saves time in cable fab.

GF70-24A429 LASER-MARKABLE ARINC 429 CABLE | WireMasters

The GF70-24A429 cable is designed per the ARINC 429 Data Bus specification. It is a suitable laser-markable alternative replacement for PIC D620224, and drop-in replacement for Carlisle 422402.

Avionics Full-Duplex Switched Ethernet

Many commercial aircraft use the ARINC 429 standard developed in 1977 for safety-critical applications. ARINC 429 utilizes a unidirectional bus with a single transmitter and up to twenty receivers.

Giga Flight Laser-Markable Arinc 429 Cable GF70-24A429

Overview Giga Flight Laser-Markable Arinc 429 Cable GF70-24A429 WARNING: Cancer and Reproductive Harm -

ARINC 429

AIT''s ARINC 429 hardware modules provide advanced features and functionality to support even the most demanding test and simulation applications.

8x DVD+/-RW 9.5mm Optical Disk Drive | Dell USA

The Optical Disk Drive Combo Drive from Dell™ allows you to enjoy crystal clear color, picture and sound clarity of CD''s and DVD''s. This Combo drive can

© 2026 EXF OPTICAL NETWORKS - All rights reserved

For communication technology Optical transmission systems POF cables ...

Optical transmission systems Two diferent connection types are used with fibre optic cables: 1. Detachable connections realised with plug connectors. In this case it is necessary to attach a plug to

Fiber Optic Cables Turned Into Hidden Microphones to Secretly Spy

Fiber Optic Cables Turned Into Microphones Fiber optic cables have long been considered inherently secure communication channels resistant to RF emissions and electromagnetic

Fiber Optic Cables | Corning

With 2 billion kilometers of fiber optic cables installed around the globe, Corning continues to lead the industry in product quality and innovation.

DS-SR429-15 r3.0

ARINC 429 to Discrete Signal Converter (SR429/1) Converting an ARINC 429 signal to discrete outputs is simple with the software-free, firmware-free SR429/1 signal converter from NEXSYS. The SR429/1

ARINC 429 vs. ARINC 664

ARINC 429 vs. ARINC 664 What''s the Difference? ARINC 429 and ARINC 664 are both communication standards used in the aviation industry, but they serve different purposes. ARINC 429 is a simple,

Avionics Full-Duplex Switched Ethernet

A highly intelligent switch, common to the AFDX network, is able to buffer transmission and reception packets. Through the use of twisted pair or fiber optic cables, full-duplex Ethernet uses two separate

HB0088: Core429 v3.12 Handbook

ARINC 429 Overview ARINC 429 is a two-wire, point-to-point data bus that is application-specific for commercial and transport aircraft. The connection wires are twisted pairs. Words are 32 bits in length

NSN 6020-01-429-3448 Fiber Optic Cable Assembly

National Stock Number (NSN) 6020-01-429-3448 fiber optic cable assembly. A definite continuous length of cable, fiber optic having both ends cleaved, optically ground and polished and/or terminated

ARINC 629

© 2026 EXF OPTICAL NETWORKS - All rights reserved

It is available in either current or optic mode, over un-shielded, twisted cables. Each terminal can send 31 word strings, and each word string can have a total of 256 words. The ARINC 629 data bus was

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://explosivefunctions.co.za
Technical inquiry: https://explosivefunctions.co.za/contact.html
EU project coordination: Parque das Nações, Lisbon, Portugal

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 EXF OPTICAL NETWORKS - All rights reserved