
Distance between distribution box and electrical equipment



Overview

Distance between distribution box and control equipmentSide clearance: There should be a minimum of 30 inches of clearance from the sides of all electrical.

Key Takeaways

A minimum working clearance of 3 feet (36 inches) in front of the distribution box is required, with at least 30 inches of width and 6. 5 feet of height, to ensure safe access and maintenance.

Working Space Requirements

The National Electrical Code (NEC) 110. 26 specifies that electrical equipment must have sufficient working space to allow safe operation, inspection, and maintenance. The depth of the working space in front of a panelboard or distribution box up to 600 volts must be at least 3 feet (914 mm), measured from the front of the equipment.

The width must be at least 30 inches (762 mm) or the width of the equipment, whichever is greater, and the height must extend from the floor to at least 6. 5 feet (2 meters) or the height of the equipment, whichever is higher. Dedicated SpaceOSHA regulations require a dedicated space around electrical equipment to protect it from damage and ensure safety.

This space should match the equipment's width and depth and extend from the floor to 6 feet (1. 83 meters) above the equipment or to the structural ceiling. No other equipment, piping, or materials should occupy this space unless protective barriers or enclosures are provided.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Protective Considerations

If the distribution box is located in areas with forklift traffic, stacked materials, or pedestrian movement, additional protection such as physical barriers may be necessary to prevent accidental contact or damage. Live parts operating at 50 volts or more must be guarded with approved cabinets or enclosures.

Summary

Depth in front of equipment: 3 feet (36 inches)Width: 30 inches (or equipment width, whichever is greater)Height: 6. 5 feet (2 meters) or equipment heightDedicated space: Floor to 6 feet above equipment, clear of unrelated objectsProtection: Barriers or enclosures if exposed to traffic or hazards Maintaining these clearances ensures compliance with NEC and OSHA standards, provides safe access for maintenance, and reduces the risk of electrical accidents or equipment damage.

Article Content

Distance between distribution box and control equipment

Side clearance: There should be a minimum of 30 inches of clearance from the sides of all electrical equipment, but in no case less than the width of the equipment itself.

Safe Clearances for Electrical Equipment: Working Space and

Side clearance: There should be a minimum of 30 inches of clearance from the sides of all electrical equipment, but in no case less than the width of the equipment itself. This is referred to

2-9-* Working space around electrical equipment

Rule 2-310 requires the minimum working space around electrical equipment to be based on the Equipment Nameplate Rating rather than the overcurrent setting. The requirements of Rules 2-308

Design of clearance and creepage distances in electrical equipment

Measures to limit transient overvoltages to the specific level are taken outside the equipment, either in the permanent installation or between the permanent installation and the equipment.

Working Clearances, based on the 2020 NEC

For indoor installations, the footprint space (width and depth of the equipment) extending from the floor to a height of 6 ft above the equipment or to the structural ceiling, whichever is lower, must be

"Reasonable and healthy matching" of site distribution box

© 2026 EXF OPTICAL NETWORKS - All rights reserved

The distance between the distribution box and the switch box shall not exceed 30m. The horizontal distance between the switch box and the electrical equipment controlled by it should not exceed 3M.

Key Points Of Installation And Collocation Of Distribution Box In ...

The wire inlets and outlets in the distribution box and switch box shall be set at the lower bottom of the box. It is strictly prohibited to set them at the top, side, back or door of the box.

Electrical Panel & Gear Clearance Guide | NEC 2023

Clearance requirements for electrical gear and panels based on NEC 2023. This guide is designed for professional electricians and electrical contractors with substantial practical experience

NEC Working Clearance Requirements: A Visual Guide (110.26)

Per NEC 110.26 (D), all working spaces must have a minimum Electrical equipment headroom of 2.0 m (6 ft 6 in), measured from the floor or platform to the ceiling or any overhead obstruction like pipes or

Clearance and creepage_UL-60950_IEC-60950_28_09_17.pdf

For equipment to be supplied from an AC MAINS SUPPLY, the value of the MAINS TRANSIENT VOLTAGE depends on the Overvoltage Category and the AC MAINS SUPPLY voltage. In general,

Fire Safety for Facilities Management Personnel – Fire Prevention ...

Where large cupboards are used for storage, but also house electrical distribution equipment, a clear space of 500 mm (half a metre) as minimum must be allowed, but a distance of

Clearances and creepage distances in LV electrical

Learn about clearances and creepage distances in LV electrical switchboards. Understand the importance of complying to IEC 61439.

Safe Clearances for Electrical Equipment: Working

Note that sufficient working space is relative to the clear space in front, between, and above electrical equipment. There are different requirements for a single row

Electrical Panel Clearance Distance FAQs

Working space or safe clearance distances are required around all electrical equipment that is likely to require examination, servicing, adjustment, or maintenance while the equipment is energized.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Electrical Panel Clearance distance

Electrical panel clearance distances are given by the U.S. NEC specifying working distance. Details are given here. This electrical wiring article series discusses procedures for safe and effective visual

A Better Understanding of NFPA 70E: Electrical Equipment Working Space

The National Electrical Code® (NEC)® Section 110.26 requires adequate working space for all electrical equipment. NEC Section 110.26 (A) requires a clear space at least 30 inches wide

Clearance and creepage_UL-60950_IEC-60950_28_09_17.pdf

AC MAINS SUPPLY: a. power distribution system external to the equipment for supplying power to a.c. powered equipment These power sources include public or private utilities and, unless otherwise

OSHA Electrical Panel Clearance Requirements: Guide

Electrical panel clearance is a critical aspect of workplace safety, ensuring that electrical equipment is accessible and maintainable without risk of injury. Proper

Contact Us

Continue your research online:

Website: https://explosivefunctions.co.za
Technical inquiry: https://explosivefunctions.co.za/contact.html
EU project coordination: Parque das Nações, Lisbon, Portugal

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 EXF OPTICAL NETWORKS - All rights reserved