Distance of the Level 3 Distribution Box from the Site



Overview

What should the distance be between the floor and the distribution board or main switch?

Approved Document M of the Building Regulations states that consumer units/fuseboxes should be mounted so that the switches are 1350-1450mm above floor level. It takes the incoming power and safely distributes it to different circuits throughout your building. While the IEC 60364 standard outlines international best practices, BS 7671 – 2018 (which is aligned with IEC standards BS EN 61439) specifically applies to the UK. Site selection requirements: The distribution box should be. The horizontal distance between switchbox and fixed electrical equipment should not exceed 3m. Generally, distribution boxes can be divided into three levels of secondary protection, that is, three levels of distribution boxes: general distribution boxes (primary distribution boxes), distribution. The distribution box on the construction site shall be equipped with outdoor general distribution box and distribution box, which shall be distributed according to three-level distribution and two-level leakage protection distribution; 2.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Article Content

IEC / BS 7671 Codes for Consumer Unit and

Residential: The recommended height for distribution board and consumer unit is between 1 metre to 1.8 metre from the floor. The suggested height is 1.3 metres

What should the distance be between the floor and the

What should the distance be between the floor and the distribution board or main switch? Approved Document M of the Building Regulations states that consumer

Requirements And Specifications For Installation Of

The bottom edge of the distribution box is usually between 1.5 meters and 1.8 meters above the ground, which is convenient for operation and

How many distance from ground when install distribution box ...

The total distribution box and switch box should be equipped with leakage protector, and the distance between distribution box and switch box, switch box and electrical equipment should

"Reasonable and healthy matching" of site distribution box

The distance between the distribution box and the switch box shall not exceed 30m. The horizontal distance between the switch box and the electrical equipment controlled by it should not exceed 3M.

What is Level 1, Level 2 and Level 3 distribution box

Three level protection refers to: on-site construction of electricity must be done in the general distribution box, distribution box and switch box to install leakage protection.

technical guidance for developers domestic electricity

Please ensure that you refer to the information contained in this document in conjunction with the approved design when preparing site for our installation works.

1. INTRODUCTION

This Code of Practice provides the details of the general principles to be applied to the design of distribution substations, including substations located at ground floor, basement, upper floor level

Regulations / guidance regarding siting of distribution

BS EN 547 series can help with this. The minimum dimensions in Section 729 of BS 7671 apply where certain specific protective measures

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Essential Rules for 3-Level Electrical Distribution

Follow key principles: no cross-level wiring, one machine-one switch, ≤30m box spacing, dry/ventilated installation for safe distribution.

What should the distance be between the floor and the

What should the distance be between the floor and the distribution board or main switch? Find out from our team of experts on Your Questions Answered by

The installation requirements for the distribution box

Learn how to install a distribution box safely and correctly. Covers wiring, placement, standards, and expert tips for a compliant setup.

Optimal Distance from Septic Tank to Distribution Box

Discover the ideal distance from a septic tank to a distribution box, including guidelines, facts, and real owner insights.

PlugShare

Find EV charging stations with PlugShare, the most complete map of electric vehicle charging stations in the world!Charging tips reviews and photos from the EV

How to determine the size, installation method and

11) When the construction site stops working for more than one hour, the power switch box shall be powered off and locked. 12) During the inspection and

The difference between the first,second,and third levels of ...

Third level distribution box: refers to the final junction box of each electrical appliance, which can be movable and fixed. Remember that the leakage protection switch is the last one, and

How many distance from ground when install distribution box ...

Distribution box and switch box should not exceed 30 meters. The horizontal distance between switchbox and fixed electrical equipment should not exceed 3m. Generally, distribution

How to confirm whether the installation location of the

Before installation, an on-site inspection should be conducted to confirm whether the installation location of the box meets the above

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Contact Us

Continue your research online:

Website: https://explosivefunctions.co.za
Technical inquiry: https://explosivefunctions.co.za/contact.html
EU project coordination: Parque das Nações, Lisbon, Portugal

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 EXF OPTICAL NETWORKS - All rights reserved