Eye diagram measurement amplitude



Overview

In, an eye pattern, also known as an eye diagram, is an display in which a from a receiver is repetitively sampled and applied to the vertical input (y-axis), while the data rate is used to trigger the horizontal sweep (x-axis). It is so called because, for several types of coding, the pattern looks like a series of eyes between a pair of rails. It is a tool for the evaluation of the combi.

Key Takeaways

Eye amplitude is the difference between the mean logic 1 and logic 0 levels in an eye diagram, representing the vertical signal swing and indicating signal quality.

Understanding Eye Amplitude

In an eye diagram, eye amplitude quantifies the vertical distance between the average high (logic 1) and low (logic 0) levels of a digital signal. It is a key indicator of signal integrity because it reflects the signal's voltage swing and the margin available for the receiver to correctly distinguish between logical states. For multi-level signals like PAM4, amplitude measurements extend to the differences between each level (0, 1, 2, 3), ensuring proper detection of all symbols.

Related Measurements

Eye Height: Measures the vertical opening of the eye at the center of the bit period, accounting for noise-induced closure. While eye amplitude is the ideal difference between logic levels, eye height reflects the usable signal margin in the presence of noise. Zero and One Levels: The mean voltage values of logical 0 and 1, used to calculate eye amplitude.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Rise and Fall Times: Transition times between logic levels, which influence the shape and vertical clarity of the eye.

Measurement Techniques

Eye amplitude is typically measured using a high-speed sampling oscilloscope or an eye pattern analyzer. The instrument samples the input signal repeatedly, superimposing multiple bit sequences to form the eye diagram. The mean values of the logic levels are extracted from the histogram of the vertical signal distribution, and the difference between these means gives the eye amplitude.

Automated software often provides simultaneous measurements of eye amplitude, eye height, and other parameters for quick signal quality assessment.

Practical Significance

A larger eye amplitude indicates a stronger signal with better noise tolerance, while a smaller amplitude suggests potential signal degradation, higher bit error rates, or insufficient voltage margin for reliable detection. Engineers use eye amplitude alongside other eye diagram metrics to diagnose issues such as attenuation, jitter, and intersymbol interference in high-speed digital systems. In summary, eye amplitude is a fundamental metric in eye diagram analysis, providing a direct measure of the vertical signal swing and helping ensure reliable digital communication.

Article Content

Understanding Eye Pattern Measurements Application Note

An eye diagram is a useful tool for understanding signal impairments in the physical layer of high-speed digital data systems, verifying transmitter output compliance, and revealing the amplitude and time

Eye pattern

OverviewCalculationModulationChannel effectsMeasurementsExternal links

In telecommunications, an eye pattern, also known as an eye diagram, is an oscilloscope display in which a digital signal from a receiver is repetitively sampled and applied to the vertical input (y-axis), while the data rate is used to trigger the horizontal sweep (x-axis). It is so called because, for several types of coding, the pattern looks like a series of eyes between a pair of rails. It is a tool for the evaluation of the combi

:MEASure:EYE:AMPLitude

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Eye amplitude is the difference between the logic 1 level and the logic 0 level histogram mean values of an eye diagram. This measurement is made in a section of the eye referred to as the eye window

Making Eye Diagram Measurements in PicoSample

You can combine eye diagram analysis with histogram measurements to get further insight into your design. The 9400 series with Picosample 4 can measure 27 vertical and 15

eyeAmplitude

For a given eye opening, eye amplitude is defined as the difference between the mean value of the symbols above and below the eye opening. It is usually calculated in a narrow window around the

Anatomy of an Eye Diagram

Learn how to construct an eye diagram via common methods of triggering used in electrical engineering to gain more insight to transmitters, channels and receivers.

Eye Measurement

The Eye Measurement block generates eye pattern from time-domain waveform data and calculates metrics from the generated pattern.

Analyzing Eye Diagrams for Signal Integrity | Sierra Circuits

In this article, you''ll learn how eye patterns are generated and how to analyze eye diagrams for signal integrity by evaluating the eye height, width, jitter, and amplitude.

Eye Diagram Basics: Reading, Analyzing and Applying

On an oscilloscope, the shape of an eye diagram will depend upon various types of triggering signals, such as clock triggers, divided clock triggers, and pattern triggers. Differences in

What is an Eye Diagram? | High-Speed Design

An eye diagram tells you everything you need to know about the behavior of signals in a high-speed channel, as well as the channel''s response to

Eye Diagram

Eye Diagram The eye diagram is another important alternative BER measurement for binary OOK systems. There are two types of noises that can impact system performance: amplitude noise and

Mastering Eye Diagrams in Optical Communications

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Learn the fundamentals of eye diagrams, their significance in optical communications, and how to interpret them for better network performance and troubleshooting.

Anatomy of an Eye Diagram

Eye Measurements Basics Eye diagrams are a very successful way of quickly and intuitively assessing the quality of a digital signal. A properly constructed eye should contain every possible bit sequence

Eye Diagram (EYE)

The Eye Diagram element can also be used as a decoder when a reference signal or bit pattern is provided. In this mode, level assignment is based on the reference/bit pattern, and not strictly on

Key Parameters Measured Using an Eye Diagram in High-Speed

An eye diagram is a powerful tool for analyzing the quality and performance of high-speed digital signals. By examining the superimposed signal transitions, several key parameters can be

Eye Height

The eye height is determined as follows: You can also choose to view eye height as a ratio of the Eye Height to Eye Amplitude measurements, which indicates how much the eye diagram has closed due

A Robust Algorithm for PAM4 Eye-Diagram Analysis

Abstract— We propose an approach for analyzing PAM4 (pulse amplitude modulation 4-level) eye diagrams that always provides a unique solution by making use of a K-Means algorithm in

Guide to Analyzing an Eye Diagram for Signal Integrity in M-PHY ...

Rise and Fall Times: Measure the time it takes for the signal to transition from low to high (rise time) and high to low (fall time). Faster transitions contribute to a cleaner eye diagram. Signal

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Additional source notes

In , an eye pattern, also known as an eye diagram, is an display in which a from a receiver is repetitively sampled and applied to the vertical input (y-axis), while the data rate is used to trigger the horizontal sweep (x-axis). It is so called because, for several types of coding, the pattern looks like a series of eyes between a pair of rails. It is a tool for the evaluation of the combi...

Contact Us

Continue your research online:

Website: https://explosivefunctions.co.za
Technical inquiry: https://explosivefunctions.co.za/contact.html
EU project coordination: Parque das Nações, Lisbon, Portugal

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 EXF OPTICAL NETWORKS - All rights reserved