FC and FC Interface Interoperation



Overview

Fibre Channel started in 1988, with ANSI standard approval in 1994, to merge the benefits of multiple physical layer implementations, including SCSI, HIPPI and ESCON.

Key Takeaways

Fibre Channel (FC) interfaces interoperate by connecting servers, storage devices, and FC switches in a SAN using standardized protocols, port modes, and addressing schemes to ensure reliable, high-speed data transfer. Overview of Fibre Channel (FC)Fibre Channel is a high-speed, lossless data transfer protocol primarily used in storage area networks (SANs) to connect servers and storage devices.

F

C networks typically form a switched fabric, where multiple FC switches operate together to provide scalable, high-performance connectivity.

F

C can run over optical fiber or copper cabling, supporting data rates from 1 Gbps up to 128 Gbps. The protocol supports upper-layer transport of SCSI, FICON, and NVMe commands, enabling block-level storage access.

FC Interfaces and Port Modes

© 2026 EXF OPTICAL NETWORKS - All rights reserved

An F

C interface is a physical or logical port on a server, storage device, or switch that transmits and receives FC frames.

F

C interfaces can operate in several modes: F_Port: Connects a single node (server or storage) to a switch. E_Port: Connects two FC switches to extend the fabric. NP_Port: Node port on a server or storage device.

Auto mode: Automatically negotiates the appropriate port type.

Each F

C interface requires a compatible FC optical module to establish a link, and the interface status can be verified via link indicators. Addressing and InteroperationFC devices use World Wide Names (WWNs) as globally unique identifiers and FC addresses (FC IDs) for communication within a fabric.

An F

C address is 24 bits long, consisting of Domain_ID, Area_ID, and Port_ID, which uniquely identify each N_Port in the fabric. This addressing allows multiple servers and storage devices to interoperate seamlessly within the same SAN.

F

C and FCoE InteroperationFibre Channel can interoperate with Fibre Channel over Ethernet (FCoE), which encapsulates FC frames over Ethernet networks. Devices supporting FCoE can connect to FC SANs through FCoE-capable interfaces, allowing integration of Ethernet and FC infrastructures while maintaining FC protocol semantics.

Configuration Example

To enable FC interface interoperation in a SAN: Install FC interface modules on switches or servers.

Connect F

C optical modules to the interfaces and verify link status. Configure port modes (F_Port, E_Port, etc.) according to the network topology. Create zones and zone sets to control access between servers and storage arrays.

Assign F

© 2026 EXF OPTICAL NETWORKS - All rights reserved

C interfaces to FC instances and activate the configuration. This setup ensures dual-plane networking for redundancy, supports multiple VN_Ports, and allows servers to access different LUNs on storage arrays reliably. SummaryFC interface interoperation relies on standardized port modes, addressing, and fabric configurations to connect servers, storage, and switches in a SAN.

Integration with FCoE allows FC traffic to traverse Ethernet networks, providing flexibility in modern data center environments. Proper configuration of FC interfaces, zoning, and link verification is essential for high-performance, reliable storage communication.

Article Content

Understanding Interfaces on an FCoE-FC Gateway

When a switch functions as an FCoE-FC gateway to connect FCoE devices on an Ethernet network to a Fibre Channel (FC) switch in a storage area network (SAN), it handles FCoE traffic from hosts and

Fibre Channel

Fibre Channel started in 1988, with ANSI standard approval in 1994, to merge the benefits of multiple physical layer implementations, including SCSI, HIPPI and ESCON. Fibre Channel was designed as

Understanding Fibre Channel | Junos OS | Juniper Networks

When configured as a Fibre Channel over Ethernet (FCoE)-FC gateway, the QFX3500 switch supports the transport of native FC traffic between FC switches and the gateway''s native FC

Fibre Channel Physical Layer Tutorial

This document describes the unique characteristics specific for FC devices as well attempts to introduce the generic topics involved in serial based technologies.

Fibre Channel Interoperability

FC components include initiators, targets, and FC-capable switches that interconnect FC devices and may also interconnect FC devices with Fibre Channel over Ethernet (FCoE) devices.

ANSI Fibre Channel Documentation

Physical and Signaling Interface (FC-PH) Rev 4.3 Physical and Signaling Interface -2 (FC-PH-2) Rev 7.4 Physical ans Signaling Interface -3 (FC-PH-3) Rev 9.1 Fabric Generic Requirements (FC-FG) Rev

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Example for Configuring an FCF (FC Interfaces)

This document describes the configurations of Trill, FC and FCoE, DCB, and NLB Server Cluster Association.

Configuring an FC or FCoE Interface

Layer 2 Ethernet interfaces can be switched to Fiber Channel (FC) interfaces. The default type of an FC interface is F_Port. A VF_Port is a virtual logical interface that is manually created on an FCoE

Storage Networking 101: Understanding Fibre Channel

They are: FC-0: The interface to the physical media; cables, etc FC-1: Transmission protocol or data-link layer, encodes and decodes signals FC-2: Network Layer; the core of FC FC-3: Common services,

ISO/IEC 14165-147:2021

Abstract This standard describes the physical interface portions of high performance optical link variants that support the higher level Fibre Channel protocols including FC-FS-4 (reference) and FC-FS-5

Fibre Channel Layers

Fibre Channel FC-2 Overview: Fibre Channel FC-2 refers to the network layer of the Fibre Channel architecture. It is responsible for providing

Understanding Fibre Channel | Junos OS | Juniper Networks

Fibre Channel (FC) is a serial I/O interconnect network technology capable of supporting multiple protocols. It is used primarily for storage area networks (SANs). The committee

Fibre Channel Routing Concepts

Fibre Channel route (FC Router) A switch running the FC-FC routing service. Refer to Supported Platforms for FC-FC Routing for the list of platforms that can be FC routers. Backbone fabric A

Solved: what is interface fc2/5?

I am from Brocade background, and new to CISCO FC swithc. Todady I have a very basic question. (config)# interface fc2/5 I could not find any document defined what 2/5 is? is this a

4.3 Overview of Fibre Channel (FC) SAN Protocol

© 2026 EXF OPTICAL NETWORKS - All rights reserved

The FC architecture represents true channel and network integration and captures some of the benefits of both channel and network technology. FC protocol provides both the channel speed

Understanding FCoE-FC Gateway Functions

Each of the native FC interfaces on the gateway performs a fabric login (FLOGI) to the FC switch when each interface initializes. This establishes the link between each gateway FC interface and the FC

Immunoglobulin Fc Heterodimer Platform Technology: From

Immunoglobulin Fc heterodimers have been engineered through modifications to the CH3 domain interface, with different mutations on each domain such that the engineered Fc fragments,

Fibre Channel over Ethernet (FCoE) Configuration Overview on Red

Fibre Channel over Ethernet (FCoE) Based on standards from IEEE T11 FC-BB-5, FCoE allows the encapsulation of Fibre Channel (FC) frames over Ethernet networks. The common data center has a

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://explosivefunctions.co.za
Technical inquiry: https://explosivefunctions.co.za/contact.html
EU project coordination: Parque das Nações, Lisbon, Portugal

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 EXF OPTICAL NETWORKS - All rights reserved