Fiber optic adapter ferrule model and specifications



Overview

For both types of optical fibers, ferrule specifications such as inner diameter (ID), outer diameter (OD), length, concentricity, radius, and bore style are important to consider. Choices for bore style include single bore, double bore, and racetrack bore. Threaded FC/APC connectors are designed for high-vibration environments and minimal back reflections. The "APC" stands for "angled physical contact" because these connectors allow the surfaces of two connected fibers to be in direct contact with each other and because the fiber end is polished at. The F-AS-KIT Single-mode adaptor kit contains a single adaptor body; FC, SC, and ST interchangeable connector tips; a universal mating sleeve for quick ferrule-to-ferrule connections; and a fiber stop to ensure that bare cleaved fibers are flush with the front of the connector ferrule. Piano wires. The 77670 SMA Fiber Bundle Ferrule is an aluminum cylinder with an 11 mm outside diameter with an SMA termination. 11 mm fiber ferrules give all our bundles a common external diameter of. Upgrade your network performance with our professional-grade Fiber Optic Connectors. Ideal for telecom, data centers, and fiber termination. PRIZM® MT and MT Elite® are ultra-high-density multi-line fiber optic ferrule designs that far surpass standard butt-joint ST type systems for both optical performance and package size in high-speed data transmission applications. 5mm Ferrules for Multimode Applications. FC, SC, ST, LC, MTP, E2000, SMA, MU, MTRJ, and more types.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Article Content

FC/APC Fiber Connectors: Single Mode

These FC/APC connectors have an 8° pre-angled ceramic ferrule, which when properly polished, results in a typical return loss of 60 dB. Each connector

F-AS-KIT Bare Fiber Adaptor Kit

The F-AS-KIT Single-mode adaptor kit contains a single adaptor body; FC, SC, and ST interchangeable connector tips; a universal mating sleeve for quick ferrule-to-ferrule connections; and a fiber stop to

77670 Ferrule Converter

This lets you use any SMA terminated single fiber with our full range of fiber bundle holders and positioners. 11 mm fiber ferrules give all our bundles a common external diameter of 11 mm (0.44 inch).

MT Ferrule Rugged High-Density PRIZM® MT

PRIZM® MT is a monolithic optical fiber ferrule that integrates microlenses and mechanical alignment features into a single component. The design provides low

Fiber Optic Adapters (Couplers), Ferrules, Sleeves

In-series couplers, between-series hybrid adapters, connector ferrules, and splice alignment sleeves. FC, SC, ST, LC, MTP, E2000, SMA, MU, MTRJ, and more types.

Optical Communications Products

Browse our optical communication connectivity products designed to help you enable your communication networks. Easily create a bill of materials list.

Fiber Optic Connectors Information

Fiber optic connectors are used to align and join two or more fibers together to provide a means for attaching to, or decoupling from, a transmitter, receiver, or any other fiber optic equipment. An

Document No

Over-polishing a TMT ferrule could impact performance in multiple ways including a significant degradation in function of the key connector components and increase in optical attenuation due to a

77670 Ferrule Converter

© 2026 EXF OPTICAL NETWORKS - All rights reserved

The 77670 SMA Fiber Bundle Ferrule is an aluminum cylinder with an 11 mm outside diameter with an SMA termination. This lets you use any SMA terminated single fiber with our full range of fiber bundle

Fiber Optic Ferrules Information

Selecting fiber optic ferrules requires a careful analysis of product specifications and features. Fiber optic components for both single-mode and multi-mode fibers are commonly available.

Fiber Connector Types: A Complete Guide (2024)

FC Connector FC stands for “ferrule connector”. It is the first fiber optic connector to use a ceramic ferrule. However, unlike the plastic-bodied SC and LC, it uses a circular screw-type fitting

Fiber Optic Connectors Figure 1

Fiber-to-fiber interconnection can consist of a splice, a permanent connection, or a connector, which differs from the splice in its ability to be disconnected and reconnected. Fiber optic connector types

Key Components & Specifications of Fiber Optic Connectors

Part 2: Introduction to Fiber Optic Cable Assembly Manufacturing Key components of Fiber Optic Connectors and Key Specifications of Connectors This article series introduces engineers and

Fiber Optic Connectors & Ceramic Ferrules | SC, LC,

High-precision Fiber Optic Connectors and Zirconia Ceramic Ferrules for superior network termination. Shop widely used types (SC, LC, FC, ST) and termination

FibreFab-Connectors-Adaptors-Brochure

FibreFabtm Established in 1992, FibreFab is a leading provider of fibre optic connectivity products used in data communications and telecommunication networks. The company designs, develops,

LC Connectors and Cable Assemblies

LC Adapters and Cable Assemblies meet the growing demand for small form factor, high-density fiber optic connectivity with simplex, duplex, single-mode and multimode options. These connectors

MT38999 Multi-Channel Connectors with MT Ferrules

Amphenol offers a multi-channel circular connector with high density MT fiber optics. This connector uses MT ferrules.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Ferrules

Ferrules Berkshire Photonics offers a range of high-performance fiber optic ferrules in different diameters of 1.25mm, 2.5mm, and 3.167mm. These ferrules are available in both ceramic and stainless steel

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://explosivefunctions.co.za
Technical inquiry: https://explosivefunctions.co.za/contact.html
EU project coordination: Parque das Nações, Lisbon, Portugal

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 EXF OPTICAL NETWORKS - All rights reserved