Power Distribution Box XL3



Overview

Metal distribution enclosure XL3 S 630 offers a usable faceplate height of 1950mm and 36-module width with functional uprights. It enables IEC 61439-2 compliant assemblies and installation of DPX3, DRX, SPX, and modular devices. Metal distribution enclosure XL3 S 630 offers a usable faceplate. Distribution box modular metal surface - Suitable for DPX3 160 - Apparatus modular Vistop less than or equal to 125 In - Number of rows: 3 - Number of modules: 72 - Height: 600 mm Width: 575 mm Depth: 147 mm XL3 160 - distribution boxes metal "ready to use" - fire Resistance according to IEC. Page 1 XL³ 160 DISTRIBUTION CABINETS THE GLOBAL SPECIALIST IN ELECTRICAL AND DIGITAL BUILDING INFRASTRUCTURES. Page 2 In accordance with its continuous improve- ment policy, Legrand reserves the right to change the specifications and illustrations common to the whole range. all with a modern. d easy steps. Only few catalogue numbers of fixing kits for XL3-N 250 cabinets are and multiple enough to cover all the professional's needs in terms of circuit breakers: MCBs up to 63 A a y: the bus ribution box. Insulated earth available t knockouts. Can be replaced with IP 41. 020182 LEGRAND XL3 BOX IP55 MONOBLOCK 400H Electric Automa. Please refer to data sheet for details. 020182 LEGRAND Brand new product in its original packaging covered by the warranties and certifications provided by LEGRAND Guarantee, repair. Surface mounting distribution cabinets - Capacity 18 modules per row - White RAL 9003 - Fully reversible cabinet (base, door and faceplates) - Supplied with : - removable and pivoting chassis with rails fitted. Rails can be individually removed for easy cabling on site - removable cable entry.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Article Content

020003 LEGRAND XL3 160 SUPERF METAL 3 ROWS

Distribution box modular metal surface - Suitable for DPX3 160 - Apparatus modular Vistop less than or equal to 125 In - Number of rows: 3 - Number of modules: 72

LEGRAND XL3 160 INSTRUCTION MANUAL Pdf

Legrand modular distribution blocks are fully insulated: they are used at the supply end of the panel up to 250 A or in subgroups of outputs in panels with a higher

XL -N 250 630

The XL3-N 630 cabinets are supplied with the fixing kits, allowing installation of MCCBs up to 630 A according to each project requirements (DRX and DPX3 ranges).

020182 LEGRAND XL3 BOX IP55 MONOBLOCK 400H Electric

XL3 400 - distribution boxes-IP 55 - IP 55 - IK 08 - Envelope-metal monoblock - Includes door blind reversible equipped with a grip of ram interchangeable (to be ordered separately) and locking legs

Distribution cabinet XL³ 125

Surface mounting distribution cabinets - Capacity 18 modules per row - White RAL 9003 - Fully reversible cabinet (base, door and faceplates) - Supplied with : -

Efficient Distribution upto 4000A

Responding to these requirements of the market, Legrand introduces the new XL3 enclosure for the LV power distribution. With its extensive range, these enclosures meet your quality standards and

enclosures XL³ 4000 and XL³ 6300 WorKshoP sPecIFIcATIo

The distribution block can be supplied directly via a vX3 busbar (with or without connection accessories, depending on the configuration) or via a head of row device.

LEGRAND XL3 S 160 Series Specifications

View and Download LEGRAND XL3 S 160 Series specifications online. DISTRIBUTION CABINETS. XL3 S 160 Series storage pdf manual download.

XL3 DO Enclosures Specifications Guide | PDF | Power

Conforming to standard IEC 61439-2, XL3 DO enclosures also feature internal arc withstand (IEC 61641) and earthquake-resistant technology (up to AG5), which

XL -N 250 630

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Optimized wiring space Extension box (optional) to be installed on XL3-N 630 distribution boards (at the top or at the bottom) for extra wiring space or additional functions. Fixing holes Pre-drilled fixing plate

PyImageSearch

Helping developers, students, and researchers master Computer Vision, Deep Learning, and OpenCV.

XL3-N 250 3-phase distribution boards

3-phase distribution boards for DIN-rail mounting circuit breakers; IP 40 (IP41 with the kit Cat.No 6 027 98) -IK 08 with door Conform to standard IEC 61439-2; Type tested; tested and certified by third part

XL-21 Low Voltage Power Distribution Panel | Up to 630A, IEC & GB

XL-21 Low Voltage Power Distribution Panel The XL-21 Power Distribution Box is used for power distribution, conversion, transmission, control, and on-site operations in low-voltage distribution

Low Voltage Fixed Electrical Power Distribution Board XL-21

XL-21 type low voltage distribution cabinet is suitable for three-phase AC 50/60HZ, max voltage 690V, rated current to 800A power distribution system,Used to control motor starting, power and lighting,

Metal Power Distribution Cabinet Box XL-21 Power

Metal Power Distribution Cabinet Box XL-21 Power Supply Box Low Voltage Power Switchgear Floor Stand Distribution Cabinet, Find Details and Price about

DISTRIBUTION CABINETS WORKSHOP

Legrand modular distribution blocks are fully insulated: they are used at the supply end of the panel up to 250 A or in subgroups of outputs in panels with a higher power rating.

Product Type

Networking Systems Deploy, organize and manage data and power distribution, indoors and outdoors.

PDF document

PDF document PDF document Read this PDF document online, download the original file, and browse related details on device.report. Additional coding instructions can be found in the Article File chapter

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Contact Us

Continue your research online:

Website: https://explosivefunctions.co.za
Technical inquiry: https://explosivefunctions.co.za/contact.html
EU project coordination: Parque das Nações, Lisbon, Portugal

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 EXF OPTICAL NETWORKS - All rights reserved