Standard for Copper Busbars in Low-Voltage Switchgear



Overview

IEC 61439 Busbar Standard: A Guide to Low-Voltage This standard defines the design verification, test requirements, and thermal performance of the assembli.

Key Takeaways

Copper busbars for low-voltage switchgear are specified based on current-carrying capacity, thermal limits, material grade, cross-sectional dimensions, and compliance with IEC 61439 and related standards.

Material and Grades

Copper busbars are typically made from ETP copper (C11000) for general applications due to its high conductivity, availability, and ease of fabrication. For applications requiring higher purity or vacuum service, oxygen-free copper (C10200) or silver-bearing copper may be used to enhance joint stability and thermal performance. Copper is preferred over aluminum for its mechanical strength, lower thermal expansion, better stiffness, and resistance to cold flow in clamped joints.

Standards and ComplianceIEC 61439-1 and 61439-2 define the design verification, thermal performance, and test requirements for low-voltage switchgear assemblies, including busbars.

IE

C 60228 provides standardized cross-sectional language for conductors, useful for busbar sizing.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

E

N 13601 and ASTM B187 define copper material requirements, dimensions, and tolerances for electrical bar stock. For North American projects, UL 1558 and IEEE C37. 20.

1 are relevant for low-voltage switchgear compliance.

Current Rating and Thermal Limits

Busbar ampacity is determined by the rated current of the system, adjusted for diversity factors, installation conditions, and environmental factors.

IE

C 61439 sets the maximum permissible busbar temperature at 140°C, which is 105 K above a 35°C ambient. A 10–15% safety margin is recommended to account for localized hot spots, high-altitude operation, or frequent load cycling. Busbar sizing often balances width, thickness, and layering to optimize thermal performance and minimize AC resistance effects.

Dimensions and Layout

Standardized 5 mm or 6 mm copper bar families are commonly used across a wide current range for modularity and thermal efficiency. Horizontal busbars serve as the main current path, while vertical busbars distribute power to outgoing units. Proper spacing and insulation are critical to prevent overheating and ensure mechanical stability.

Cross-sectional area must be derated for enclosure heating, bar grouping, orientation, surface finish, and allowable conductor temperature.

Installation Considerations

Copper busbars should be supported with repeatable insulating hardware to maintain mechanical integrity. Bolted joints are preferred for reliability, and care must be taken to avoid cold flow or loosening over time. Heat dissipation, electromagnetic compatibility, and corrosion resistance are also key factors in design verification.

Summary

When specifying copper busbars for low-voltage switchgear, engineers must consider material grade, cross-sectional dimensions, current-carrying capacity, thermal limits, and compliance with IEC 61439 and related standards. Proper design ensures safe, reliable, and efficient power distribution, while standardized busbar families and careful layout improve modularity, manufacturability, and long-term performance.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Article Content

IEC 61439 Busbar Standard: A Guide to Low-Voltage

This standard defines the design verification, test requirements, and thermal performance of the assemblies. The IEC 61439 standard applies to

Low Voltage Switchgear Design for US and EU

This guide explains horizontal and vertical busbar design, current density logic, IEC and North American standards, and how E-abel builds reliable

Busbar Standards: Design, Installation & IEC 61439

What standard governs busbar sizing in low voltage panels? For low-voltage assemblies, IEC 61439-1 is the main framework because it governs

IEC 61439 Low Voltage Switchgear Design: Complete 2026 Guide

The IEC 61439 standard series, which replaced IEC 60439 in 2009, represents a fundamental shift in how low voltage switchgear assemblies are designed, verified, and certified.

IEC 61439 Standards-R1

Rated impulse withstand voltage, referred to as Uimp, is the peak value of an impulse voltage of prescribed form and polarity that the equipment is capable of withstanding without failure under

IEC Standard for Busbar Sizing: IEC 61439 Requirements

Learn the IEC standard for busbar sizing as per IEC 61439, including current-carrying capacity, temperature rise limits, and design criteria for safe and

Copper for Busbars

Although busbar systems should normally be designed for lowest lifetime cost – which means a lower working temperature to reduce waste energy costs – the ability of copper to maintain its mechanical

Busbar Design in Switchgear: Key Principles & Best

Looking for a safe, efficient, and standards-compliant busbar solution for your switchgear project? Our engineering team can help you choose the right

IEC 61439 standard for low voltage switchgear and controlgear ...

IEC 60439, the standard for low-voltage switchgear and controlgear assemblies, was under restructuring from the last decade. The new series of IEC 61439 standards were published in

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Copper Busbar Size And Current Rating | GRL Copper

IEC 61439 (which replaced IEC 60439) is the primary international standard governing low-voltage switchgear and controlgear assemblies, including their busbar systems.

Busbar Jointing and Torque Guidelines | PDF | Screw | Welding

The document provides specifications for electrical switchgear assembly, including: 1) Tables listing recommended bar widths, lengths of overlap, bolt sizes, hole diameters, and minimum tightening

Price Of High Voltage Enclosed Busbars In Uzbekistan

Sell Price Of High Voltage Enclosed Busbars In Uzbekistan in bulk to verified buyers and importers. Connect with businesses actively looking to buy wholesale Price Of High Voltage Enclosed Busbars

Common Busbar Failures: Causes, Diagnosis Methods & Proven

Industry Standards to Be Adhered to IEC 61439 (Low-voltage switchgear assemblies) IEC 60865 (Short-circuit forces) IS 8623 / IS 8084 Adherence to standards minimizes the chances of failure. Selecting

Low Voltage Distribution Systems Market in the United Arab Emirates ...

The United Arab Emirates Low Voltage Distribution Systems market encompasses the equipment and integrated solutions used to distribute electrical power at voltages up to 1,000 V AC

Busbars and Connectors in HV and EHV installations

Connection design must comply with: Contact area standards for temperature rise (e.g., IEC 61439) Material compatibility treatments (e.g., tin-plating for copper-aluminum transitions) Mechanical

Switchgear Insulation Testing: The Definitive Field Guide

Switchgear is different. A single switchgear panel contains: Busbars — copper or aluminum conductors running the length of the assembly Circuit breaker — the switching device,

EMS | ⚡ Individual Busbars for Switchgear

Solid busbars Solid busbars are used as central distributors in switchgear. In order to achieve the lowest possible voltage drop or transport loss, conductive

Switchboard Busbar Guide (2025): Design & Standards

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Switchboard Busbar: Design, Standards, and Selection Guide Busbars are the backbone of a low-voltage switchboard: rigid conductors that

Contact Us

Continue your research online:

Website: https://explosivefunctions.co.za
Technical inquiry: https://explosivefunctions.co.za/contact.html
EU project coordination: Parque das Nações, Lisbon, Portugal

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 EXF OPTICAL NETWORKS - All rights reserved