
The characteristics of G652 standard single-mode optical fiber



Overview

The standard specifies the geometrical, mechanical, and transmission attributes of a single-mode optical fibre as well as its cable. The fibre has zero-dispersion wavelength around 1310 nm as per how it was designed, however it can also be used in the 1550 nm wavelength region.

Key Takeaways

G. 652 is the standard single-mode optical fiber optimized for 1310 nm operation, with variants like G. 652.

D supporting full-spectrum low-loss transmission including the 1550 nm region. OverviewG. 652 is an international ITU-T standard for single-mode optical fiber (SMF), first developed in 1984 and revised multiple times, most recently in 2024.

It specifies the geometrical, mechanical, and transmission attributes of the fiber and its cable, making it the most widely deployed SMF globally. The fiber is designed with a zero-dispersion wavelength around 1310 nm, but it also supports operation in the 1550 nm region, making it suitable for both analogue and digital transmission systems. SubcategoriesG.

652 fiber has four main subcategories: G. 652. A and G.

652. B: Legacy fibers optimized for 1310 nm, with higher attenuation in the E-band (1360–1460 nm), making them less suitable for wavelength-division multiplexing (WDM) applications. G.

652. C and G. 652.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

D: Modern fibers with reduced water peak, allowing low-loss operation across the full spectrum (1270–1625 nm). G. 652.

D is the most current and widely used variant, optimized for WDM and long-haul networks. All subcategories share a core size of 8–10 µm, but differ in attenuation, macrobending loss, polarization-mode dispersion (PMD), and mode field diameter (MFD) specifications.

Key Characteristics

Wavelength Optimization: Zero-dispersion near 1310 nm; low-loss operation at 1550 nm. Attenuation: Typically 0. 35 dB/km at 1310 nm and 0.

22 dB/km at 1550 nm for G. 652. D.

Macrobending Loss: Reduced in G. 652. D to support tighter installation radii.

Polarization-

Mode Dispersion (PMD): Specified for all categories, with stricter limits in modern variants. Mode Field Diameter (MFD): Approximately 8–10 µm, ensuring compatibility with standard SMF connectors and splicing. ApplicationsG.

652 fibers are widely used in: Telecommunication networks: Metro, long-haul, and access networks.

FTT

H (Fiber to the Home) deployments.

WD

M systems: Especially G. 652. D, which supports full-spectrum operation without water peak limitations.

High-speed digital transmission: Compatible with 10 Gbps, 40 Gbps, and 100 Gbps systems. SummaryG. 652 single-mode fiber is the standard SMF for modern optical networks, with G.

652. D being the preferred variant for full-spectrum, low-loss, and WDM-compatible applications. Its combination of low attenuation, controlled dispersion, and mechanical reliability makes it suitable for a wide range of telecommunication and data network deployments.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Article Content

ITU-T Rec. G.652 (11/2009) Characteristics of a single-mode optical ...

Recommendation ITU-T G.652 describes the geometrical, mechanical and transmission attributes of a single-mode optical fibre and cable which has zero-dispersion wavelength around 1310 nm.

G.652 Single-Mode Fiber: Characteristics and Applications

This article will provide a detailed introduction to the structure, characteristics, and applications of standard single-mode fiber (G.652) in the communication field.

What Is G.652 Fiber? G.652 vs G.652.D, G.652 vs G.655

G.652 fiber is designed to have a zero-dispersion wavelength near 1310 nm, therefore it is optimized for operation in the 1310nm band and can also operate at 1550 nm. The first edition of

Recommendation ITU -T G.652 (08/2024)

Characteristics of a single-mode optical fibre and cable Summary Recommendation ITU-T G.652 describes the geometrical, mechanical and transmission attributes of dispersion wavelength around

ITU-T G.652: Single-Mode Optical Fiber Characteristics

ITU-T G.652 Recommendation details single-mode optical fiber and cable characteristics, including geometrical, mechanical, and transmission attributes.

Single-Mode Fiber Cable Guide: Types, Specs & Selection

Complete guide to single-mode fiber optic cables: G.652, G.657.A1/A2, OS1/OS2 specs, attenuation values, applications (telecom, FTTH, data center). Includes IEC 60793-2-50 compliant

G.652 Fiber: Differences and Applications of Each Subcategory

What is G.652 Fiber? G.652 is a type of optical fiber designed for carrying a single mode of light, which means it is ideal for long-distance, high-capacity communication networks. It is

Differences Between G.652, G.655, and G.657 Fiber

Technical comparison of G.652, G.655 and G.657 fibers including refractive profiles, bending performance, dispersion, and application use cases.

Optical Fiber Types

© 2026 EXF OPTICAL NETWORKS - All rights reserved

The ITU administers the commonly referenced single-mode fiber standards documents, G.652 through G.655, as required by telecom systems manufcturers and their customers.

G.652 : Characteristics of a single-mode optical fibre and cable

Recently posted - Search Recommendations G.652 : Characteristics of a single-mode optical fibre and cable

Handbook Optical fibres, cables and systems

In particular, Recommendation ITU-T G.652 specifies the characteristics of a single-mode optical fibre operating at 1 300 nm. Recommendation ITU-T G. 957 specifies the characteristics of optical

Optical Fiber Specifications: A Guide by EXA Infrastructure

G652D is a specific variant of the G.652 standard for optical fiber cables. It is an enhanced version of standard single-mode fiber (G.652) that offers improved performance characteristics. The "D" in

G654-E Fiber Cable Specifications | PDF | Optical Fiber | Optics

Blue, orange, green brown (4 tubes for G654-E fiber) and the remaining 4 tubes for G652-D their color should be as per the standard Cable marking: Meter - Telecom Egypt – Vendor Company - Month -

Distributed Fiber Optic Vibration Sensing (DVS) System

1. What is Distributed Fiber Optic Vibration Sensing (DVS)? Distributed Fiber Optic Vibration Sensing (DVS) is an advanced optical sensing technology that uses

7 Optical Fiber Standards: G.651 to G.657 Explained

Key takeaways: G.651: Multimode fiber. G.652 to G.657: Single mode fibers. Most Commonly Used: G.652 and G.657. Understanding these ITU-T standards ensures a unified international ...

Quality Bulk Multimode & Single Mode Fiber Optic Cables

Bulk Fiber Optic Cable - Multimode & Singlemode Shop our diverse range of bulk fiber optic cables, tailored for various networking needs. We provide both single

G657A2 at US$22/km: Understanding the Optical Fiber

The number dominating every procurement manager"s spreadsheet in February 2026 is US$ 22/km for G657A2 fiber. Just six months ago, this figure

G652D vs G657A1, G657A2, G657B2/B3 – Single-mode Fiber Guide

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Compare G652D, G657A1, G657A2, and G657B2/B3 single-mode fibers. Learn their bend radius, applications, and how to choose the right fiber for FTTH and telecom.

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Additional source notes

The standard specifies the geometrical, mechanical, and transmission attributes of a single-mode optical fibre as well as its cable. The fibre has zero-dispersion wavelength around 1310 nm as per how it was designed, however it can also be used in the 1550 nm wavelength region.

Contact Us

Continue your research online:

Website: https://explosivefunctions.co.za
Technical inquiry: https://explosivefunctions.co.za/contact.html
EU project coordination: Parque das Nações, Lisbon, Portugal

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 EXF OPTICAL NETWORKS - All rights reserved