What are the interfaces of the FC block



Overview

Fibre Channel is standardized in the of the International Committee for Information Technology Standards (), an (ANSI)-accredited standards committee. Fibre Channel started in 1988, with ANSI standard approval in 1994, to merge the benefits of multiple physical layer implementations including, and. Fibre Channel was designed as a to overcome limitations of the SCSI and HIPPI physic.

Key Takeaways

Fibre Channel (FC) block interfaces include physical ports (N_Port, F_Port, E_Port), protocol layers (FC-0 to FC-4), and service interfaces for connecting servers and storage in SANs.

FC Protocol Layers and Interfaces

Fibre Channel is structured into five layers, each providing specific interfaces: FC-0 (Physical Layer): Defines the physical media and connectors, including optical fiber or copper cables, transceivers, and signal encoding (8B/10B). Devices connect via physical ports at this layer, which handle the transmission and reception of raw data signals. FC-1 (Data Link Layer): Provides reliable frame delivery, error detection, flow control, and data framing.

Interfaces at this layer ensure that frames are transmitted in order and without errors. FC-2 (Network Layer): Manages the transport of frames between nodes, including addressing, routing, and switching. This layer interfaces with the fabric to deliver frames to the correct destination.

© 2026 EXF OPTICAL NETWORKS - All rights reserved

FC-3 (Common Services Layer): Offers optional services such as multicast, encryption, or advanced functions shared across multiple ports. FC-4 (Upper Layer Protocol Mapping): Maps higher-level protocols like SCSI (FCP), FICON, or NVMe over FC. This layer interfaces with storage applications and operating systems to transport block-level commands.

FC Port Types and Interfaces

Fibre Channel devices use specific port types to interface with the SAN fabric: N_Port (Node Port): Connects an end device (server or storage) to the fabric. It initiates or receives I/O commands. F_Port (Fabric Port): Connects an N_Port to a switch, providing a single point-to-fabric interface.

E_Port (Expansion Port): Connects two FC switches to expand the fabric, enabling inter-switch communication. G_Port (Generic Port): Can function as either an E_Port or F_Port depending on the connection. VF_Port (Virtual Fabric Port): Used in NPIV (N_Port ID Virtualization) to allow multiple virtual N_Ports on a single physical port.

L_Port (Loop Port): Connects devices in an arbitrated loop topology, either as NL_Port (node loop port) or FL_Port (fabric loop port),.

Summary

The F

C block interfaces combine physical connectivity, protocol layers, and port types to provide high-speed, lossless, in-order block data transport in SANs. Physical ports (N, F, E, L) connect devices and switches, while the layered protocol stack (FC-0 to FC-4) ensures reliable data delivery and compatibility with upper-level storage protocols like SCSI, FICON, and NVMe.

Article Content

Fibre Channel

OverviewHistoryEtymologyCharacteristicsTopologiesLayersPortsMedia and modules

Fibre Channel is standardized in the T11 Technical Committee of the International Committee for Information Technology Standards (INCITS), an American National Standards Institute (ANSI)-accredited standards committee. Fibre Channel started in 1988, with ANSI standard approval in 1994, to merge the benefits of multiple physical layer implementations including SCSI, HIPPI and ESCON. Fibre Channel was designed as a serial interface to overcome limitations of the SCSI and HIPPI physic

Fibre Channel Overview

© 2026 EXF OPTICAL NETWORKS - All rights reserved

The basic building blocks of an FC connection are the Frames. The Frames contain the information to be transmitted (Payload), the address of the source and destination ports and link control information.

Fundamentals of Fibre Channel

It is a high-speed fibre channel topology in which fibre channel ports/hubs use arbitration to establish a point-to-point circuit and prevent multiple ports/hubs from sending frames at

Fibre Channel frame

The basic building blocks of an FC connection are the frames. They contain the information to be transmitted (payload), the address of the source and destination ports and link control information.

Overview of Fibre Channel | Junos OS | Juniper Networks

FC components include initiators, targets, and FC-capable switches that interconnect FC devices and may also interconnect FC devices with Fibre Channel over Ethernet (FCoE) devices.

4.3 Overview of Fibre Channel (FC) SAN Protocol

FC protocol provides both the channel speed for data transfer with low protocol overhead and the scalability of network technology. FC provides a serial data transfer interface that operates

Fibre Channel Interfaces

Fibre Channel is structured as a set of hierarchical functions, similar to the ISO OSI Reference Model. There are five layers, each being responsible for a certain set of functions or capabilities:

FIBRE CHANNEL

Fibre Channel will allow simultaneous transmission of different protocols over a single optical-fiber pair and it can allow a number of existing services, such as network, point-to-point, and peripheral

Fibre channel, fiber channel, layers, ports, fc topologies

The 3bit block is encoded to 4 bits and the 5bit block is encoded to 6 bits. These are then combined to form the new 10bit encoded value that is sent over the fiber optic cable to the other device as shown

31 Cool Website Animations Examples And Effects for

Check our list of 31 website animation examples and effects. Get inspired and start using web animations!

© 2026 EXF OPTICAL NETWORKS - All rights reserved

UDS Explained

In this tutorial to the UDS protocol (Unified Diagnostic Services) you''ll learn about the UDS frame structure, services, CAN ISO TP - with practical UDS data

Figure 4 from RF-Power Induced Clock Jitter Degradation and Its ...

Fig. 4. Geometric illustration for consideration of maximum jitter with linear rising-edge clock and sinusoidal RF noise source. - "RF-Power Induced Clock Jitter Degradation and Its Modeling in

ZU48/47/43/28/27/25DR RFSoC System on Module

Zynq UltraScale+ ZU48/47/43/28/27/25DR RFSoC System on Module featuring a compact 82mm x 100mm(BRYN) form factor.

EU Right of Withdrawal 2026: What Retailers Need to Know

On June 19, 2026, a small button becomes a legal requirement across the European Union. Every retailer that sells to EU shoppers will need to offer a clearly labeled, persistently

What is Fibre Channel? History, layers, components and design

Why Fibre Channel? Fibre Channel offers point-to-point, switched and loop interfaces to deliver lossless, in-order, raw block data. Because Fibre Channel is many times faster than SCSI, it

LPDDR5 Tutorial: Deep dive into its physical structure

In this tutorial we explore the physical structure of the LPDDR5 memory and understand Channels, Bank/BankGroup, Ranks and IOs

Inside a Modern Fibre Channel Architecture – Part 1

FC-0 the physical interface (FC-0) consists of transmission media, transmitters, and receivers and their interfaces physical media, associated drivers and receivers capable of operating

TIA Portal: Programming using function FC

This video will show how to:- create the FC - declare the FC''s block interface (i/o parameter and local data)- call the FC into main programming block (OB1)M...

Additional source notes

© 2026 EXF OPTICAL NETWORKS - All rights reserved

Fibre Channel is standardized in the of the International Committee for Information Technology Standards (), an (ANSI)-accredited standards committee. Fibre Channel started in 1988, with ANSI standard approval in 1994, to merge the benefits of multiple physical layer implementations including , and .
Fibre Channel was designed as a to overcome limitations of the SCSI and HIPPI physic…

Contact Us

Continue your research online:

Website: https://explosivefunctions.co.za
Technical inquiry: https://explosivefunctions.co.za/contact.html
EU project coordination: Parque das Nações, Lisbon, Portugal

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 EXF OPTICAL NETWORKS - All rights reserved